

■ Main Application

For communication equipment, ISDN, SDH, WiMAX, LTE etc.

■ Features

- A ceramics-package (Dimensions : 7.0×5.0mm).
- Output level: CMOS
- Frequency range : 1.25MHz to 62MHz
- Low current consumption : Max. 10mA




Pb Free

RoHS Compliant
Directive 2011/65/EU

■ Specifications

Item	Model	NV7050SF
Nominal Frequency Range [f] (MHz)		1.25 to 62
Standard Frequency (MHz)		2.048, 10, 25, 30.72, 38.4, 50, 61.44
Supply Voltage [V _{cc}] (V)		+3.3 ± 10 %
Current Consumption (mA)		Max. 10
Output Level		CMOS
Symmetry (%)		45 to 55 (1/2 V _{cc})
Output Load Condition (pF)		15
Operating Temperature Range (°C)		-40 to +85
Storage Temperature Range (°C)		-55 to +125
Overall Frequency Tolerance		Max. ±50 × 10 ⁻⁶
Frequency Control Range / Control Voltage [V _{cont}]		Min. ±100 × 10 ⁻⁶ / +1.65 ± 1.65 V
Frequency Change Polarity		Positive
Specification Number		NSA3527A

■ Dimensions



■ List of Stand-by function

Input (#2)	Output (#4)
High Level (Min. 0.7 V _{cc}) or OPEN	Output
Low Level (Max. 0.3 V _{cc})	Hi-Impedance

Please specify the model name, frequency, and specification number when you order products.
For further questions regarding specifications, please feel free to contact us.